# Efforts to Reduce Lead by the Industrial Community: A Regional Perspective

RCRA National Meeting
January 16, 2002
Washington, DC

Noah Borenstein
Waste Minimization Team
Waste & Chemicals Management Division
Region III




### Outline

- Region 3 Landscape
- Regional Waste Minimization Program
- Waste Minimization Success Stories:
  - Sylvin Technologies: PVC compounder
  - Signode Eastern Operations: steel strapping
  - Corning Asahi: glass for TV and computer monitors
  - American Video Glass: glass for CRTs



### Lead & Lead Compounds - Region 3 States


(Basis: TRI 1998)



NOTE: The "Waste Minimization Priority Quantity" is the quantity being measured to meet GPRA goals (50% reductions by 2005)

# Lead and Lead Compounds - Region 3 States Waste Min Priority Quantities (pounds)

Total: 9,053,813



Basis: 1998 Toxics Release Inventory

Region 3 Facilities - Lead & Lead Compounds **Lead Quantities** <10,000 lbs ## Pittsburgh 10,000 - 50,000 lbs 50,001 - 200,000 lbs Harrisburg 200,001 - 1,125,000 lbs Philadelphia >1,125,000 lbs **Major Cities** Wilmington & Baltimore Washington Charleston Richmond Roanøke

# Region III Waste Minimization Implementation Team

PADEP
Glenn Mitzel
Vu Tran

DNREC
Jane Frank
Umesh Hattikudur

MDE
Niel Thompson
Lawrence Miloscia

EPA Region III

Tad Radzinski


Noah Borenstein

Alberto Roybal

DC/EHA
Nick Kauffman

WV DEP
Carroll Cather
Wilma Reip

VA DEQ
Bill Sarnecky
Ron Pinkoski
Michael Bahorsky
John Handzo
Lewis Pillis



Reducing Toxics in Our Nation's Waste

## Waste Minimization Team Support Services


- Waste Minimization Site Visits
- Site Visit Report
- Source Reduction Strategy Development
- Technical Information / Resources
- Education / workshops
- Recognition





### Sylvin Technologies, Inc. Denver, PA (SIC 3087)

- Manufacturer of flexible to semi-rigid PVC and PVC alloy compounds
- Overall Process:



- Lead-related Process:
  - Lead (and cadmium) compounds are used as heat stabilizers in PVC processing

### Sylvin Technologies, Inc. (cont.)

Pollution Prevention/Waste Minimization Initiatives:

Material substitution:



to reduce the use of lead (and cadmium) compounds from the manufacture of wire and cable, and electrical molding products.

- In 1996, completely eliminated the use of cadmium
- All new customers: only offered non-leaded stabilized compounds
- Current customer base: converting to non-leaded products; only supply lead-stabilized if customers demand it

### Sylvin Technologies, Inc. (cont.)

### Data (TRI):

Lead Compounds (lbs.)	1994	1999	Percent change
RCRA Waste	15,228	6,153	- 59.6
Off site recycled	11,450	6,073	- 47.0
On site Treatment/ off site Disposal	2,389	80	- 96.7



### ► Accomplishments:


- ✓ Production more than doubled (1994-1999)
- ✓ Lead-stabilized products dropped from 75% to 68%
- ✓ Goal = 10% by 2005
- ✓ By 1996, eliminated cadmium-stabilized products



### Signode Eastern Operations

Baltimore, MD (SIC 3499)

- Manufacturer of low-carbon and high carbon steel, and plastic strapping systems used in industrial packaging
- Overall process



- Lead-related Process: Surface preparation
  - steel straps are passed through a molten lead bath
  - excess lead is wiped off by charcoal bed.



# Signode Eastern Operations (cont.)

- Facility generates an average of 142,000 lbs of lead:
  - lead-containing charcoal waste (shipped off site for disposal)
  - lead dross produced in molten bath (shipped off site to recycler)
- Waste Minimization Initiatives:
  - Process modification
    low-carbon steel straps (1/2001)
    - eliminated molten lead bath and charcoal wipe
    - replaced it with iron phosphate pretreatment
    - reduced number of gas-fired burners from 11 to 1
    - eliminated scrubber system



### Signode Eastern Operations (cont.)

Process modification challenge:
 customer acceptance that product quality is not affected

### Accomplishments:




- Eliminated 100,000 lbs. of lead from molten bath
- ✓ Eliminated 24,000 lbs. of lead per year (17% reduction).
- ✓ Saved over \$40,000 annually in energy savings
- ✓ This is one of three sister plants already converted.

TOTAL = 300,000 lbs. of molten lead 72,000 lbs. per year of lead \$120,000 per year in energy



### Corning Asahi Video Products Co. State College, PA (SIC 3229)

- Manufacturer of tube components for television and computer monitors, including face plates (panels), funnels, necks and neck tubing.
- Overall Process:




#### Lead-related Process:

- Lead compounds are incorporated into the glass recipe of both panel and funnel components.
- Lead provides shielding from high energy radiation emanating from the completed cathode ray tube (CRT)

# Corning Asahi Video Products Co. (cont.)

- Waste Minimization Initiatives:
  - Material substitution:



replaced lead oxide with zirconium oxide in the panel glass recipe (1998/1999)

Recycling:

high lead-containing electrostatic precipitator (EP) dust and funnel edge grind back to mixing/melting operations



## Corning Asahi Video Products Co. (cont.)

### Data (TRI):

Lead Compounds (lbs.)	1991	2000
Air releases	9,465	4,306
Water releases	240	169
On site recycled	840,000	23,443,000
Off site disposal	740,835	379,069

### ► Accomplishments:


- ✓ Production almost doubled (1991-2000)
- ✓ Air releases decreased by 55%
- ✓ Water releases decreased by 30%
- ✓ Off site disposal decreased by 49%



### **American Video Glass**

Mt. Pleasant, PA (SIC 3229)

- Manufacturer of glass panels and funnels; (components of TV picture tubes) [JV: Corning Asahi Video Products Co. and SonyElectronics (1997)]
- Overall Process:




#### Lead-related Process:

- Lead compounds are incorporated into the glass recipe of both panel and funnel components.
- Lead provides shielding from high energy radiation emanating from the completed cathode ray tube (CRT)



### American Video Glass (cont.)

- Waste Minimization Initiatives:
  - Material substitution:



replaced lead oxide with zirconium oxide in the panel glass recipe

- Recycling:
  - electrostatic precipitator (EP) dust (2/99)
  - post-consumer recycling center (de-manufacturing)



### American Video Glass (cont.)

### ► Data (TRI):

Lead Compounds (lbs.)	1997	1998	1999
Recycled (On site/off site)	0	147,720	382,904
Disposal (off site)	579,985	324,115	33,800

### ► Accomplishments:

- ✓ While production <u>increased</u> by ~20% (1997-2000), disposal <u>decreased</u> by >95%.
- ✓ Since 3/99, savings in raw materials and from waste disposal amounted to more than \$560,000.
- Currently, practically all of the lead waste is recycled.
- ✓ PBT Cup award winner in 1999

### Summary

- Lead & lead compounds have been identified as <u>important</u> <u>priorities</u> of the Waste Mimization Program.
- Progressive companies have embarked on very successful waste minimization efforts utilizing: material substitution, process modifications, and recycling techniques.
- These efforts have achieved significant reductions of these compounds in the wastes and have reduced the operating costs of these companies.

WASTE = LOST PROFITS!